



The Staircase People

Staircase kits delivered direct to you
We're part of the Designer Stairs.com group

Additional Components Chart for: Ehleva Vector Modular Open Staircase Kit

| | | | | Additional Components | | | | |
|------------------------|---------|---------|-------------------|---|-----|-----|-----|---|
| Staircase Height in cm | | Rises | Additional Treads | Optional External Railing Kits for open side of staircase | | | | |
| EU Regs | UK Regs | | | 70L | 70U | 83L | 83U | |
| 350-373 | 290-350 | 16 | +3 | 6 | 7 | 6 | 7 | |
| 326-349 | 272-328 | 15 | +2 | 6 | 7 | 6 | 7 | |
| 303-326 | 254-306 | 14 | +1 | 6 | 7 | 6 | 7 | |
| STANDARD KIT | 236-302 | 236-284 | 13 | Standard Kit with 13 risers | 5 | 6 | 5 | 6 |
| | 218-278 | 218-262 | 12 | - | 5 | 5 | 5 | 5 |
| | 200-254 | 200-240 | 11 | | 5 | 5 | 5 | 5 |

Tread rise is adjustable from 18 to 23.5cm. Tread going adjusts from 20-23cm (V70), 22-25cm (V83)

This design of balustrading does not comply with UK Building Regs' 100mm gap rule. Please note that it is your responsibility to determine if your installation is subject to the Building Regulations. If you would like advice, please feel free to contact our team to discuss your project – 01380 723533.

Maximum tread rise is 22cm for dwellings to UK Regs

The going of the treads is adjustable. See the configuration drawings for more info in the Information Centre pages.