

Description

- ▲ The standard Zen kit comprises of 11 treads and 12 risers; the last tread is set one rise down from the landing floor.
- ▲ The standard Zen kit is 610mm in width and can achieve a floor to floor height between 2310mm – 2800mm. However a maximum height of up to 3510mm can be achieved by the use of additional tread kits.
- ▲ Each individual rise can be adjusted between 193mm to 234mm to achieve a desired height.
- ▲ The Zen can be installed as a 'straight flight' or incorporate a turn at the bottom of the stair.
- ▲ The metalwork is only available in White (RAL 9010).
- ▲ The alternating Birch Plywood / Beech (laminated) treads are only available in a Dark Havana colour.
- ▲ The Zen is supplied with a balustrade (comprises of vertical balusters, stainless steel rods & a beech handrail). It can be fixed to either side of the Zen stair kit.
- ▲ A second balustrade is available for the Zen stair kit when it is not positioned against a wall.
- ▲ Optional upper floor balustrade kits are also available, these are 1200mm in length and will match the Zen stair balustrade.



Zen Stair Heights

Staircase Height	No. of Treads	No. of Risers	Additional Tread Kits Required
2120 mm - 2570 mm	10	11	-
2310 mm - 2800 mm *	11	12	-
2500 mm - 3040 mm	12	13	1
2690 mm - 3270 mm	13	14	2
2880 mm - 3510 mm	14	15	3

* Standard Kit